

## Hydrogen Analyzer—Better solution for Green Hydrogen!

### Overview

Thermal conductivity gas transmitter (analyzer) has ***built-in temperature and humidity measurement and compensation***, is cost-effective and suitable for stable and continuous measurement of the content of hydrogen (H<sub>2</sub>).

### Application

- Water electrolysis to produce hydrogen
- Hydrogenation unit
- Hydrogen-cooled generator
- University and research
- Metal heat treatment/welding
- Chemicals/Pharmaceuticals
- Air Separation Unit



### Parameters

Measuring principle	Thermal conductivity (TCD)
Display	1.8" industrial color LCD, 160*128Pixel
LED Light	Status LED Light
Linearity	< 1% of range
Repeatability	< 1% of range
Sensitivity	0.02%
T90-time	<1sec at flow rate higher 60l/h
Power	D—19 ~ 28V DC Power
Analog Output	4~20mA
Relay Output	3 Relays, NO, 5A 250VAC/30VDC
Communication	RS485, MODBUS RTU
Electrical protection	EMI / RFI CEI-EN55011 – 05/99
Flow rate	40l/h to 150l/h; 60l/h -80l/h recommended
Process Pressure(Max.)	10Bar
Temperature Range	-40 ~ 85°C
Humidity Range	0~95%RH (non-condensing)
Process Connection	G3/8 screw or 6mm tube
Ambient Temperature	-15 ~ 60°C
Housing Material	Aluminum and Stainless steel
Explosion-proof	Exd IICT4 Controller optional

## Hydrogen Analyzer——Better solution for Green Hydrogen!

Note:

MZD reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail.

MZD does not accept responsibility for potential errors or possible lack of information in this document.

